



MODEL: HyperMol 1000W **WATTS** 1000W
VOLTAGE: 110 - 277V **SKU** IL-HMEFX-1000


TECHNICAL SPECS

Rated Voltage	AC 110 - 277V
Power Consump	1000W ± 5%
Power Supply	Sosen LED Drivers
PPF	2900 μmol/s
Efficacy	2.9 μmol/J
LED Spectrum	Full Spectrum
Power Factor	>0.9
Control	Dimmer / 0-10V input and output
Frequency	60Hz
Ambient Temperature - Working	0°C - 35°C / 32° - 95°F
Light Distribution - Beam Angle	120 Degree
Waterproof Rating	IP65
LED Lifespan (90% of Life)	50000 hours
Daisy Chain	Max. 45 * fixtures by daisy chain
Light Source	Samsung LM281B+ Pro * 2800 pcs 4000K LED+ Honglitronic SMD3535 660nm * 240 pcs




PHYSICAL SPECIFICATIONS



Height 115mm / 4.5"
Weight - N.W./G.W. 16.5kg/17.5kg | 36.37bs / 35.7lbs



SPECTRUM



CONTROL DIAGRAM



5 YEAR WARRANTY



www.iluminarlighting.com 1-877-540-5588 sales@iluminarlighting.com
© Copyright 2025 ILUMINAR Lighting. Subject to change without notice.