



CMH

# 630W

## DE REMOTE BALLAST

VOLTAGE:

SKU:

120V/240V

IL-RMCDE630-120

277V

IL-RMCDE630-277



### INPUT SPECIFICATIONS

	120V	240V	277V
Input Current	5.56A	2.79A	2.4A
Input Power	675W	665W	665W
Output Power	630W		
Min Power Factor	0.95		
THD	<15%		
Crest Factor	<1.7		
BTU	126		
Inrush Current	≤ 37.5 Amps		

### PROTECTIONS


- End of Lamp Life (EOL) Protection
- Short Circuit Protection
- Open Circuit Protection
- Ignition Failure Protection
- Thermal Protection

### OUTPUT SPECIFICATIONS


	120V/240V	277V
Rated Voltage	120V/240V	277V
Voltage Range (+/-10%)	108-264V	249V-305V
Plug Type	Male NEMA 6-15	Male NEMA L7-15 Twist Lock
Dimming Type	50%-75%100%-110%-EXT	
Frequency	50/60Hz	
Operation Temp.	140-220HZ	
Max. Temperature	0 - 35°C / 32-95°F	
Relative Humidity	85%	
Max. Humidity	95%	
Remote Mounting	5m/16ft	
Ignition Voltage	5kV	

### PHYSICAL SPECIFICATIONS

Case Length	271mm	10.67"
Case Width	204mm	8.05"
Height	124mm	4.88"
Weight	4.2kg	9.26lb



204mm / 8.05"



271mm / 10.67"

124mm / 4.88"



iluminarlighting.com  
Toll Free: 1-877-540-5588

**3**YEAR  
WARRANTY

© Copyright 2022 ILUMINAR Lighting  
Subject to change without notice.