



# 750W

## DE REMOTE BALLAST

MH/HPS

**VOLTAGE:**

120V/240V

**SKU:**

IL-RMDE750-240

277V

IL-RMDE750-277



**INPUT SPECIFICATIONS**

	120V	240V	277V
Input Volts	6.7A	3.5A	2.91A
Input Current	805W	795W	790W
Output Power	750W		
Min Power Factor	0.99		
THD	<10%		
Crest Factor	<1.7		
BTU	150		
Inrush Current	≤ 37.5 Amps		

**PROTECTIONS**


- End of Lamp Life (EOL) Protection
- Short Circuit Protection
- Open Circuit Protection
- Ignition Failure Protection
- Thermal Protection

**OUTPUT SPECIFICATIONS**


Rated Voltage	120V/240V	277V
Voltage Range (+/-10%)	108-264V	249V-305V
Plug Type	Male NEMA 6-15	Male NEMA L7-15 Twist Lock
Dimming Type	400-500-600-750-825-EXT	
Frequency	50/60Hz	
Operational Frequency	100-120Hz	
Operation Temp	0 - 35°C / 32-95°F	
Relative Humidity	85%	
Max. Humidity	95%	
Remote Mounting	5m/16ft	
Ignition Voltage	5kV	

**PHYSICAL SPECIFICATIONS**

Case Length	275mm	10.83"
Case Width	178mm	7.01"
Height	113mm	4.45"
Weight	3.5kg	7.71lb



178mm / 7.01"



275mm / 10.83"

113mm / 4.45"

iluminarlighting.com  
Toll Free: 1-877-540-5588

**3 YEAR**  
WARRANTY



© Copyright 2022 ILUMINAR Lighting  
Subject to change without notice.