



1030W
iLogic^{FS}
PLUS

MODEL: ILOGIC FS PLUS

WATTS 1030W

VOLTAGE: 100 - 277V

SKU ILL1030FS

TECHNICAL SPECS



Rated Voltage	100 - 277V
Power Consump	1030w ± 5%
Power Supply	Sosen LED Drivers
PPF	3446 μmol
Efficacy	3.12 μmol/J
LED Spectrum	Full Spectrum
Min Power Factor - Power Factor	>0.9
THD	< 10%
Crest Factor	< 10%
BTU	3500
Frequency	60Hz
Dimming	0 - 100% dimming via RS485
Ambient Temperature - Working	0°C - 35°C / 32° - 95°F
Relative Humidity	< 90%
Color Temperature	4000K
Color Rendering Index	85
Emitting Cooling	Aluminum heatsink
Light Distribution - Beam Angle	120 Degree
Waterproof Rating	IP65
LED Lifespan	50000 hours
Daisy Chain	Max. 256 LED fixtures for output A and output B individually
Light Source	Samsung LM281B+Pro White LED * 3640 pcs Honglitrionic SMD3535 660nm * 280 pcs

VOLTAGE AND AMPERAGE


Voltage	120V	208V	220V	240V	277V
Amperage	8.59A	4.96A	4.69A	4.30A	3.72A

PHYSICAL SPECIFICATIONS

Height	75 mm / 2.9"
Weight - N.W./G.W.	14.5kg / 16.5kg 32lbs / 36.3lbs
Package Size	1130*625*85mm / 44.5*24.6*3.3"



SPECTRUM



This commercial fixture requires a separately purchased Plus Controller to operate.

5 YEAR
WARRANTY




www.iluminarlighting.com 1-877-540-5588 sales@iluminarlighting.com


© Copyright 2024 ILUMINAR Lighting. Subject to change without notice.

PPF MAP


Height of
12" / 30CM PAR Distribution



Height of
24" / 60CM PAR Distribution



Height of
31" / 80CM PAR Distribution



Height of
39" / 100CM PAR Distribution

