



MODEL: ILOGIC MS PLUS

WATTS 1050W

VOLTAGE: 100-277V


SKU IL-L1050MS

TECHNICAL SPECS

Rated Voltage	100-277V
Power Consump	1050W±5%
Power Supply	Sosen LED Drivers
ePAR - PPF	3446 μmol/s
ePAR Efficacy - Efficacy	3.05 μmol/J
LED Spectrum	Full Spectrum + UV + IR
Min Power Factor - Power Factor	>0.9
THD	< 10%
Crest Factor	< 10%
BTU	3500
Frequency	60Hz
Dimming	0-100% dimming via RS485
Ambient Temperature - Working	0°C - 35°C / 32° - 95°F
Color Temperature	4000K
Color Rendering Index	85
Relative Humidity	<90%
Emitting cooling	Aluminum heatsink
Light Distribution - Beam Angle	120 Degree
Waterproof Rating	IP65
LED Lifespan (90% of Life)	50000 hours
Daisy Chain	Max. 256 LED fixtures for output A and output B individually
Light Source	Samsung LM281B+ Pro * 3640pcs Honglitrionic SMD3535 660nm * 280pcs Honglitrionic SMD3030 (UV) * 192pcs Honglitrionic SMD2835 (IR) * 192pcs

PHYSICAL SPECIFICATIONS


Height 75 mm/2.9"
 Weight - N.W./G.W. 15kg/17kg | 33lbs/37.4lbs
 Package Size 1130*625*85mm / 44.5*24.6*3.3"




VOLTAGE AND AMPERAGE

Voltage 120V 208V 220V 240V 277V
 Amperage 8.75A 5.05A 4.78A 4.38A 3.79A


SPECTRUM




Full Spectrum 100% ON.




Full Spectrum ON 100% + UV 100% ON.




Full Spectrum 100% ON + FR 100% ON.




Full Spectrum 100% ON + UV 100% ON + FR 100% ON.





UV 100% ON.



FR 100% ON.



UV 100% ON + FR 100% ON.



5 YEAR WARRANTY



www.iluminarlighting.com 1-877-540-5588 sales@iluminarlighting.com

© Copyright 2024 ILUMINAR Lighting. Subject to change without notice.